



SPH-170

63/4

Order No.: 0100110

Price upon request

PRODUCTINFOS

Hi-fi bass-midrange speaker, 50 W, 8 Ω

- Speaker of very high quality with extensive equipment
- Round aluminium diecast basket with recessed screw head holes
- Inverse rubber surround
- Drilled pole core
- · Cone with excellent damping
- Exceptionally deep bass reproduction for any bass and bass-midrange application

HOBBY HiFi 04/2017

"Incredibly linear and wideband sound pressure frequency response. The ideal speaker for high-quality 2-way systems."

TECHNICAL SPECIFICATIONS



SPH-170

Impedance (Z) 8 Ω

Frequency range f3-5,000 Hz

Resonant frequency (fs) 38 Hz
Power rating (RMS) 50 W
Peak music power output (MAX) 80 W

Sensitivity 90 dB/W/m

Suspension compl. (Cms) 1.43 mm/N

Moving mass (Mms)12.5 gMech. Q factor (Qms)2.38Electr. Q factor (Qes)0.55

Total Q factor (Qts) 0.44
Equivalent volume (Vas) 37 I

DC resistance (Re) 6.2 Ω

Force factor (BxL) 5.90 Tm

Voice coil induct. (Le) 0.45 mH

Voice coil diameter Ø 25 mm

Voice coil former aluminium

Linear excursion (X_{MAX}) \pm 3 mm

Eff. cone area (Sd) 137 cm^2 Magnet weight 370 g

Magnet diameter Ø 100 mm

Mounting cutout Ø 150 mm

Mounting depth 73 mm

Dimensions Ø 185 mm x 80 mm

6.75"

Outside diameter Ø 185 mm

Width Ø 185 mm

Depth 80 mm

Admiss. ambient temp. 0-40 °C

Weight 1.3 kg

Packing unit 1

Type of speaker

dB Ω 100 90 80

SPH-170 (10.0110)



